




HEALTHCARE



HALO Smart Sensor is Multi-Patented
and Design is Trademarked



HALO Smart Sensor

our all-in-one health, safety and vape device.

HALO is a key component in the solution to providing a low-risk environment by monitoring Carbon Dioxide (CO₂), Particulate Concentrations, Humidity, Volatile Organic Compounds (VOC), and Nitrogen Dioxide (NO₂) in the air. **HALO** delivers safe, healthy, and comfortable environments that keeps all personnel safe while, at the same time, saving money by efficiently running the HVAC system.



DISEASE PREVENTION

Ensure your residents and staff are safe from airborne diseases, prevent the spread of infectious disease, ensure rooms have been cleaned, and the air is properly filtered.



VAPE AND MARIJUANA (THC) DETECTION

Identify vaping and THC usage in privacy areas such as patient rooms, bathrooms, break rooms, and common areas.



PANIC BUTTON

Users can trigger alerts via an external 3rd party panic button or via the HALO cloud app. The location of the trigger is associated to the HALO device in closest proximity.



MOTION DETECTION

Receive trespassing alerts when movement is detected in unauthorized areas and after hours.



AIR QUALITY MONITORING

See the average of the quality of the air you are breathing over the course of a few hours. Automate and ensure proper ventilation in each room with BACnet integration.



CHEMICAL AND GAS DETECTION

Catch chemical spills and hazardous gases in mechanical or utility rooms, custodial closets, and maintenance areas.



AGGRESSION DETECTION

Protect your staff and customers. With HALO you are able to detect fights and loud noises in usually quiet areas.



CUSTOM SENSOR OPTIONS

Need customized calibrated industrial sensors? HALO 3C has options for Ozone, Sulfur Dioxide, Hydrogen Sulfide, Nitrogen Dioxide, and more!

Key Features

HEALTH



Health Index



Air Quality Index



Carbon Monoxide



Carbon Dioxide



Nitrogen Dioxide



Relative Humidity



Temperature



TVOC



Particulates



Chemicals

SAFETY



Help
(Spoken Keyword)



Panic Button



Aggression



Two-Way
Communication



Gunshot



Motion



Occupancy
(People Counter)



Emergency Escape
& Alert Lighting



Tamper

VAPE



THC



Vape



Vape Masking

Connect to HALO Cloud to manage multiple devices, receive real-time Health Index and AQI alerts and reporting, see alerts and historical data to document your buildings health status and trouble areas.
Download the HALO Cloud App to receive push notifications!



General Specifications

Operating Temperature 32°F - 122°F (0°C - 50°C)

Operating Humidity 0 to 90% Relative Humidity (non-condensing)

Power Supply **Single HALO 3C**, PoE (IEEE 802.3af Class 3 Compliance) 11W. HALO 3C with **additional tethered HALO 3C**, PoE (IEEE 802.3at Class 3 Compliance) 22W*

Dimensions 5.5" x 2.0" (140mm x 51mm)

Weight 0.8 lbs (0.365 kgs)

Mounting Options Surface Mount, Pole Mount (optional), Conduit Adapter (optional)

Vandal IK10 rated, vandal proof housing with Tamper Alert

Certifications UL, CUL, CE, RoHS, FCC, WEEE, NRCS, ACMA, RCA, UKCA, VCCI, KC

Easier Installation with 3C

- Surface Mount Installation
- Power TWO Units Using One Cable Run*

Network Specifications

Ethernet In RJ-45 (10/100 Base-T)

Ethernet Out RJ-45 (10/100 Base-T) IEEE 802.3af Class Compliance

Protocols BACnet, RTSP, TCP/IP, IPV4/V6, HTTP, HTTPS, DHCP, ARP, Bonjour

Wireless 2.4 GHZ and 5GHZ IEEE 802.11 b/g/n/ac Wireless

Bluetooth Bluetooth 5.0, BLE

Interface Specifications

Live Display Resolution* 1024 x 768, IFPS, Live MJPEG or H264, 8 Users maximum

Audio MEMS Microphones (2) [Audio Analysis Only] No Recording of Live Stream

Alarm Triggers Air Quality Index (AQI), Health Index, Vape, Vape THC, Aggression, Gunshot, Spoken Keyword, Tamper, Particulates, Carbon Dioxide Calibrated, Total Volatile Organic Compounds, Carbon Monoxide, Temperature/Humidity, Light Level, Sound Levels, Building Health, Motion Detection, Occupancy (People Counter), Panic Button

Output 1, Normally Open or Closed, 48VDC at 1 amp

Input 1, Isolated

RS-485 1, Integrates wired industrial sensors

External Device Power Output 5VDC out at 300mA

Status Light Alarm Condition, Multi-Color, Programmable

Speaker Alarm Condition, Pre-Recorded Files, Programmable WAV Files

**Image display of sensor readings only.*

VMS Integrations: Milestone, Genetec, Avigilon, ExacQ Vision, Rhombus Systems, Arculus, Vivotek, Pelco, Ganz Control, Nx Witness, Qognify, DW Spectrum IPVMS, Mirasys, Video Insight, EoCortex, Wisenet Wave VMS, Axonsoft, Digifort, and many others!

Supported Languages: English, Foreign Languages Supported

Other 3rd Party Integrations: Reflow+ Metasys and OpenBlue, The Boring Lab, Presence Management, iIdentifyED, Vigilance Software, Punch Alert, DIR-S, Extreme Network Defender, Aruba HPE, Connect One, AMT, Gallagher, NuLEDs, Singlewire Informacast and many others!

Emergency Key Words: HALO supports multiple key words